



TECHNICAL DATA SHEET BSA 532 CONTACT ADHESIVE

DESCRIPTION: BSA 532 is a flammable contact adhesive formulated to be resistant to plasticizer migration. This adhesive contains no VOCs and is HAPs free.

TYPICAL PHYSICAL PROPERTIES:

Base:	Nitrile
Flammability:	Flammable
Solvent:	Acetone
Viscosity:	200-400 cPs
Solids:	28% +/- 2%
Color:	Translucent
Density:	7.15 Pounds per Gallon
Heat Resistance:	210° F
Open Time:	30 minutes @ 70° F, depending on substrates
Bonding Time:	After dry to the touch
Shelf Life:	12 months in an unopened, sealed container

APPLICATIONS:

- Carpet to Wood
- Vinyl to Wood, Metal or Fiberglass
- Fabric to Wood, Plastic, Metal or Fiberglass
- Bonds to a variety of other substrates

GENERAL INFORMATION:

Spray, roll or brush grade

Designed to be a two-way adhesive

- Apply to both surfaces being bonded
- Allow the adhesive to achieve tack
- Bring both surfaces to be bonded together
- Apply ample pressure to insure full contact of substrates

Clean up with acetone and/or toluene

Temperature, humidity and air movement can and does affect open time

Prior to use, read the MSDS for health and safety details

Data provided is that of a typical lot/batch

NON-WARRANTY:

Recommendations for the use of products are based upon tests believed by us to be reliable. However, since the handling and use of our products under user's conditions are beyond our control, no warranty, expressed or implied, including but not limited to merchantability or fitness for a particular use, is made concerning this product. The user assumes all risks of use or handling, whether or not in accordance with any directions or suggestions of the supplier. Seller shall not be liable to purchaser or any other person for loss or damage directly or indirectly arising from the use of our products, from breach of any warranty or from any other cause, the exclusive remedy against the seller being to require replacement or repair of defective goods. If the purchaser does not accept our products on such terms, they are to be returned at once, unopened. For professional and industrial use only - Not for resale.